



General information

| | |
|-------------------------|------------------------|
| Product ID | 5907577475864 |
| GTIN | 5907577475864 |
| Manufacturer name | OSPEL |
| Manufacturer short name | OSPEL |
| Manufacturer product ID | GP-1GZ/m/18 |
| Net length | 0.14 m |
| Net width | 0.09 m |
| Net height | 0.05 m |
| Net weight | 0.072 kg |
| Net volume | 630000 mm ³ |
| Discount group ID | Podstawowa |
| Bonus group ID | Podstawowa |
| PKWiU | 27.33.13.0 |
| Customs commodity code | 8536 69 90 |

ETIM description

| | |
|------------------------------------|---------------------------------------|
| Class | Socket outlet (EC000125) |
| Group | Domestic switching devices (EG000013) |
| Model | Earthing pin |
| Protective contact | Round |
| Number of active contacts (round) | 2 |
| Number of active contacts (flat) | 0 |
| Number of active contacts (square) | 0 |
| With signal lamp | No |
| Number of socket outlets | 1 |

| | |
|--|------------------------------|
| Number of modules (module system) | 1 |
| Number of socket outlets switchable | 0 |
| Number of phases | 1 |
| Imprint/indication | None |
| Connection type | Screwed terminal |
| With hinged lid | No |
| With enhanced contact protection | No |
| Label space/information surface | No |
| Colour | Silver |
| RAL-number (similar) | 9006 |
| Transparent | No |
| Lockable | No |
| Eject-mechanism | No |
| Insulated mounting | No |
| With function lighting | No |
| With orientation lighting | No |
| Overvoltage protection | No |
| Fault current protection | No |
| With miniature fuse | No |
| Mounting method | Flush-mounted |
| Type of fastening | Mounting with claw and screw |
| Material | Plastic |
| Material quality | Thermoplastic |
| Halogen free | Yes |
| Surface protection | Lacquered |
| Surface finishing | Glossy |
| Anti-bacterial treatment | No |
| With loop through function | No |
| With on/off switch | No |
| Rotated central insert | No |
| Nominal current | 16 [A] |
| Nominal voltage | 250 [V] |
| Frequency | 50..60 [Hz] |
| Suitable for degree of protection (IP) | IP20 |
| Impact strength | IK03 |
| Device width | 75 [mm] |
| Device height | 75 [mm] |
| Device depth | 37 [mm] |

Ordering information

| | |
|------------------|-----|
| Order unit | One |
| Minimum quantity | 1 |

| | |
|-----------------------|-----|
| Quantity interval | 1 |
| Content unit | One |
| Content unit quantity | 1 |

Packing information

| | |
|-------------------------|-----|
| Packing unit code | One |
| Quantity of order units | 4 |

Attachments

| | |
|----------------------|---|
| Product data sheet | https://epim.one/product-card/pdf/4YcrZOZngF5ulFOT91b4miho26W8MBat/lang/en |
| Product data sheet | https://epim.one/product-card/pdf/4YcrZOZngF5ulFOT91b4miho26W8MBat/lang/pl |
| Main product picture | https://files.epim.one/pekra/foto/gp-1gz_m_18.jpg |

Related product

| | |
|--------------------|---------------|
| Related product ID | 5907559808482 |
| Relation type | Accessory |