



General information

Product ID	5905339338846
GTIN	5905339338846
Supplier	Kanlux
Manufacturer name	KANLUX
Manufacturer short name	KANL
Manufacturer product ID	33884
Brand name	Kanlux
Net length	0.314 m
Net width	0.243 m
Net height	0.04 m
Net weight	1.264 kg
Net volume	3052080 mm <sup>3</sup>

ETIM description

Class	Downlight/spot/floodlight (EC001744)
Group	Luminaires (EG000027)
Suitable for surface mounting	Yes
Suitable for built-in mounting	No
Suitable for wall mounting	Yes
Suitable for suspended mounting	Yes
Suitable for ceiling mounting	Yes
Suitable for traverse mounting	No
Suitable for pedestal/floor mounting	Yes
Suitable for light-track mounting	No
Suitable for clamp-mounting	No

Suitable for low voltage cable system	No
Adjustability	Swivelling
With movement sensor	No
With light sensor	No
Lamp type	LED not exchangeable
With light source	Yes
Suitable for number of light sources	1
Housing material	Aluminium
Surface protection	Powder coating
Housing colour	Black
Material cover	Glass opal
Surface brushed	No
Voltage type	AC
Nominal voltage	220..240 [V]
Type of control gear	LED operating device voltage-controlled
With control gear	Yes
Exchangeable control gear	No
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI-2	No
Dimming DALI	No
Dimming DMX	No
Dimming DSI	No
Dimming potentiometer (integrated)	No
Dimming LineSwitch	No
Dimming manufacturer's proprietary system	No
Dimming mains voltage modulation	No
Dimming phase cut-off (trailing edge)	No
Dimming phase cut-on (leading edge)	No
Light distributor	Reflector
Light outlet	Direct
Rated lifetime L70/B50 at 25 °C	50000 [h]
Impact strength	IK07
Protection class according to IEC 61140	I
Rated ambient temperature according to IEC 62722-2-1	-30..50 [°C]
Suitable for lamp power	90..90 [W]
Max. system power	90 [W]
Colour of light	White
Colour temperature	4000..4000 [K]
Colour rendering index CRI	80-89
Rated luminous flux according to IEC 62722-2- 1	12000..12000 [lm]
Power factor	0.9

Length	314 [mm]
Width	243 [mm]
Height/depth	38 [mm]
Type of wiring	Ending
Number of poles	3
Connection type	Other

## Ordering information

Order unit	One (unit)
Minimum quantity	1
Quantity interval	1
Content unit	One (unit)
Content unit quantity	1

## Attachments

Data sheet	<a href="https://epim.one/product-card/pdf/FCNJeHcpznePuW0oJdKAGBjkFjzAZvXk/lang/en">https://epim.one/product-card/pdf/FCNJeHcpznePuW0oJdKAGBjkFjzAZvXk/lang/en</a>
Data sheet	<a href="https://epim.one/product-card/pdf/FCNJeHcpznePuW0oJdKAGBjkFjzAZvXk/lang/pl">https://epim.one/product-card/pdf/FCNJeHcpznePuW0oJdKAGBjkFjzAZvXk/lang/pl</a>
Main product picture	<a href="https://files.epim.one/pekra/foto/33884.jpg">https://files.epim.one/pekra/foto/33884.jpg</a>

## Related product

Related product ID	8592920035160
Relation type	Accessory