



General information

Product ID	5908312594017
GTIN	5908312594017
Alt. product ID by supplier	BIS-411
Manufacturer name	FiF
Manufacturer short name	FF
Manufacturer product ID	BIS-411
Net length	0.095 m
Net width	0.07 m
Net height	0.02 m
Net weight	0.05 kg
Net volume	133000 mm ³

ETIM description

Class	Latching relay (EC000188)
Group	Devices for distribution board-/surface mounting (EG000062)
Function	Electronic switch
Mounting method	DIN rail
Width in number of modular spacings	1
Built-in depth	70 [mm]
Number of contacts as normally open contact	0
Number of contacts as normally closed contact	0
Number of contacts as change-over contact	1
Control voltage 1	230..230 [V]
Type of control voltage 1	AC
Frequency control voltage 1	50..50 [Hz]

Control voltage 2	0..0 [V]
Type of control voltage 2	AC
Frequency control voltage 2	0..0 [Hz]
Rated switch current	0.005 [A]
Supply voltage	230..230 [V]
Voltage type (supply voltage)	AC
Max. incandescent lamp load	600 [W]
Max. load fluorescent lamp	300 [VA]
Max. load fluorescent lamp (Duo circuit)	300 [VA]
Max. load fluorescent lamp (parallel compensated)	200 [VA]
Suitable for manual operation	No

Ordering information

Order unit	One (unit)
Minimum quantity	1
Quantity interval	1
Content unit	One (unit)
Content unit quantity	1

Attachments

Data sheet	https://epim.one/product-card/pdf/HyDG2eLxHkOO0HySI9baJWSNSBDGLIP3/lang/en
Data sheet	https://epim.one/product-card/pdf/HyDG2eLxHkOO0HySI9baJWSNSBDGLIP3/lang/pl
Declaration (other)	https://files.epim.one/etimone/FF/UE_FF003_18_BIS_dek_zgod_CE.pdf
Main product picture	https://files.epim.one/pekra/FF/FF_BIS-411.jpeg
Manual	https://files.epim.one/etimone/FF/FF_BIS-411_230V_inst_D170425_PL.pdf
Others	http://www.fif.com.pl/przekazniki-bistabilne/42-przekaznik-bistabilny-bis-411-230-v.html