



General information

| | |
|-------------------------|------------------------|
| Product ID | 5907577425784 |
| GTIN | 5907577425784 |
| Manufacturer name | OSPEL |
| Manufacturer short name | OSPEL |
| Manufacturer product ID | GN-1BZ/00 |
| Net length | 0.15 m |
| Net width | 0.105 m |
| Net height | 0.06 m |
| Net weight | 0.057 kg |
| Net volume | 945000 mm ³ |
| Discount group ID | Podstawowa |
| Bonus group ID | Podstawowa |
| PKWiU | 27.33.13.0 |
| Customs commodity code | 8536 69 90 |

ETIM description

| | |
|------------------------------------|---------------------------------------|
| Class | Socket outlet (EC000125) |
| Group | Domestic switching devices (EG000013) |
| Model | Earthing pin |
| Protective contact | Round |
| Number of active contacts (round) | 1 |
| Number of active contacts (flat) | 0 |
| Number of active contacts (square) | 0 |
| With signal lamp | No |
| Number of socket outlets | 1 |

| | |
|--|------------------------------|
| Number of modules (module system) | 0 |
| Number of socket outlets switchable | 0 |
| Number of phases | 1 |
| Imprint/indication | None |
| Connection type | Screwed terminal |
| With hinged lid | No |
| With enhanced contact protection | No |
| Label space/information surface | No |
| Colour | White |
| RAL-number (similar) | 9003 |
| Transparent | No |
| Lockable | No |
| Eject-mechanism | No |
| Insulated mounting | No |
| With function lighting | No |
| With orientation lighting | No |
| Overvoltage protection | No |
| Fault current protection | No |
| With miniature fuse | No |
| Mounting method | Surface mounted |
| Type of fastening | Mounting with claw and screw |
| Material | Plastic |
| Material quality | Thermoplastic |
| Halogen free | Yes |
| Surface protection | Untreated |
| Surface finishing | Glossy |
| Anti-bacterial treatment | No |
| With loop through function | No |
| With on/off switch | No |
| Rotated central insert | No |
| Nominal current | 16 [A] |
| Nominal voltage | 250 [V] |
| Frequency | 50..60 [Hz] |
| Suitable for degree of protection (IP) | IP20 |
| Impact strength | IK03 |
| Device width | 60 [mm] |
| Device height | 60 [mm] |
| Device depth | 38 [mm] |

Ordering information

| | |
|------------------|-----|
| Order unit | One |
| Minimum quantity | 1 |

| | |
|-----------------------|-----|
| Quantity interval | 1 |
| Content unit | One |
| Content unit quantity | 1 |

Packing information

| | |
|-------------------------|-----|
| Packing unit code | One |
| Quantity of order units | 10 |

Attachments

| | |
|----------------------|---|
| Product data sheet | https://epim.one/product-card/pdf/Jw23ANiKeyRdYopLhDwMV1ZiSHAnDiOl/lang/en |
| Product data sheet | https://epim.one/product-card/pdf/Jw23ANiKeyRdYopLhDwMV1ZiSHAnDiOl/lang/pl |
| Main product picture | https://files.epim.one/pekra/foto/gn-1bz_00.jpg |