

# VOLTA Sp. z o. o.



## General information

|                                 |                       |
|---------------------------------|-----------------------|
| Product ID                      | 1040969               |
| GTIN                            | 9010238060845         |
| Supplier                        | Eaton Corporation PLC |
| Product ID by supplier          | 194694                |
| Manufacturer name               | EATON                 |
| Manufacturer product ID         | 194694                |
| Net length                      | 0.085 m               |
| Net width                       | 0.085 m               |
| Net height                      | 0.085 m               |
| Net weight                      | 0.1 kg                |
| Discount group ID               | PDC-MCB*/EATON        |
| Bonus group ID                  | LiniowyQ/EATON        |
| Warranty for consumer customers | 24 [month]            |
| Warranty for business customers | 24 [month]            |

## ETIM description

|                                      |                                                    |
|--------------------------------------|----------------------------------------------------|
| Class                                | Residual current circuit breaker (RCCB) (EC000003) |
| Group                                | Circuit breakers and fuses (EG000020)              |
| Number of poles                      | 4                                                  |
| Rated voltage                        | 230 [V]                                            |
| Rated current                        | 40 [A]                                             |
| Rated fault current                  | 0.03 [A]                                           |
| Rated insulation voltage Ui          | 440 [V]                                            |
| Rated impulse withstand voltage Uimp | 4 [kV]                                             |
| Mounting method                      | DIN rail                                           |
| Leakage current type                 | AC                                                 |

|                                                    |               |
|----------------------------------------------------|---------------|
| Selective protection                               | No            |
| Short-time delayed tripping                        | No            |
| Short-circuit breaking capacity (I <sub>cn</sub> ) | 6 [kA]        |
| Surge current capacity                             | 0.25 [kA]     |
| Voltage type                                       | AC            |
| With interlocking device                           | Yes           |
| Frequency                                          | 50 Hz         |
| Additional equipment possible                      | Yes           |
| Degree of protection (IP)                          | IP20          |
| Width in number of modular spacings                | 4             |
| Built-in depth                                     | 45 [mm]       |
| Ambient temperature during operating               | -25..40 [°C]  |
| Pollution degree                                   | 2             |
| Connectable conductor cross section multi-wired    | 1.5..16 [mm²] |
| Connectable conductor cross section solid-core     | 1.5..35 [mm²] |
| Explosion-proof                                    | No            |

## Ordering information

|                       |       |
|-----------------------|-------|
| Order unit            | Piece |
| Minimum quantity      | 1     |
| Quantity interval     | 1     |
| Content unit          | Piece |
| Content unit quantity | 1     |

## Pricing information

|                  |             |
|------------------|-------------|
| Price quantity   | 1           |
| Price on request | Yes         |
| Price currency   | PLN (Zloty) |
| VAT              | 0.23        |
| Territory        | Poland      |

## Attachments

|                      |                                                                                                                                                                                                                                                     |
|----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product data sheet   | <a href="https://epim.one/product-card/pdf/JzjLKppzi45Fpluf5fDWF1jextd718FG/lang/pl.pdf">https://epim.one/product-card/pdf/JzjLKppzi45Fpluf5fDWF1jextd718FG/lang/pl.pdf</a>                                                                         |
| Product data sheet   | <a href="https://files.epim.one/volta/EATON/eaton_194694_karta.pdf">https://files.epim.one/volta/EATON/eaton_194694_karta.pdf</a>                                                                                                                   |
| Main product picture | <a href="https://files.epim.one/volta/EATON/eaton_194694.jpeg">https://files.epim.one/volta/EATON/eaton_194694.jpeg</a>                                                                                                                             |
| Others               | <a href="https://files.epim.one/volta/B2C/GPSR_Wylaczniki_nadpradowe_i_aparatura_zabezpieczajaca_instalacje_elektryczne.pdf">https://files.epim.one/volta/B2C/GPSR_Wylaczniki_nadpradowe_i_aparatura_zabezpieczajaca_instalacje_elektryczne.pdf</a> |