



General information

| | |
|-------------------------|-------------------------|
| Product ID | 8595665314118 |
| GTIN | 8595665314118 |
| Supplier | Kanlux |
| Manufacturer name | KANLUX |
| Manufacturer short name | KANL |
| Manufacturer product ID | 31411 |
| Brand name | Kanlux |
| Net length | 1.2 m |
| Net width | 0.064 m |
| Net height | 0.06 m |
| Net weight | 0.84 kg |
| Net volume | 4608000 mm ³ |
| Discount group ID | Brak |
| Bonus group ID | Brak |
| Customs commodity code | 94054039 |

ETIM description

| | |
|---------------------------------------|------------------------------------|
| Class | Ceiling-/wall luminaire (EC002892) |
| Group | Luminaires (EG000027) |
| Suitable for wall mounting | Yes |
| Suitable for suspended mounting | No |
| Suitable for ceiling mounting | Yes |
| Suitable for built-in mounting | No |
| Suitable for surface mounting | Yes |
| Suitable for light line configuration | No |

| | |
|---|----------------------|
| Lamp type | LED not exchangeable |
| With light source | Yes |
| Suitable for number of light sources | 1 |
| Lamp holder | Other |
| Housing material | Plastic |
| Surface protection housing | Untreated |
| Housing colour | Grey |
| Material cover | Plastic, opal |
| Type of grid | None |
| Voltage type | AC |
| Nominal voltage | 220..230 [V] |
| Nominal current | Unknown |
| Exchangeable control gear | No |
| Dimming 0-10 V | No |
| Dimming 1-10 V | No |
| Dimming DALI | No |
| Dimming DALI-2 | No |
| Dimming DMX | No |
| Dimming DSI | No |
| Dimming manufacturer's proprietary system | No |
| Dimming mains voltage modulation | No |
| Dimming phase cut-off (trailing edge) | No |
| Dimming phase cut-on (leading edge) | No |
| Dimming programmable | No |
| Dimming potentiometer (integrated) | No |
| Dimming RF | No |
| Dimming Touch and Dim | No |
| Dimming Zigbee | No |
| Dimming with push-button | No |
| Light distributor | Unknown |
| Light distribution | Symmetric |
| Beam angle | Unknown |
| Colour consistency (McAdam ellipse) | Unknown |
| Light outlet | Unknown |
| Rated lifetime L70/B50 at 25 °C | 20000 [h] |
| Lumen maintenance at median useful life of 35,000 h at 25 °C ambient (tq) | Unknown |
| Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq) | Unknown |
| Lumen maintenance at median useful life of 75,000 h at 25 °C ambient (tq) | Unknown |
| Failure rate at median useful life of 35,000 h at 25 °C ambient (tq) | Unknown |

| | |
|---|-----------------|
| Failure rate at median useful life of 50,000 h at 25 °C ambient (tq) | Unknown |
| Failure rate at median useful life of 75,000 h at 25 °C ambient (tq) | Unknown |
| Max. number of luminaires per miniature circuit breaker B16 (MCB) | Unknown |
| Max. number of luminaires per miniature circuit breaker C16 (MCB) | Unknown |
| Degree of protection (NEMA) | Unknown |
| Impact strength | IK08 |
| Protection class according to IEC 61140 | II |
| Rated ambient temperature according to IEC 62722-2-1 | -20..40 [°C] |
| Suitable for emergency lighting | No |
| With movement sensor | No |
| With light sensor | No |
| Covering of the luminaire with thermally insulating material possible | No |
| With air slots | No |
| Filament test according to IEC 60695-2-11 | Not applicable |
| Max. system power | 36 [W] |
| Rated luminous flux according to IEC 62722-2- 1 | 3600..3600 [lm] |
| Colour of light | White |
| Colour temperature | 4000..4000 [K] |
| Flickering value Pst LM | Unknown |
| Colour rendering index CRI | 80-89 |
| Power factor | Unknown |
| Stroboscope effect value SVM | Unknown |
| Constant light output (CLO) | No |
| Width | 64 [mm] |
| Height/depth | 60 [mm] |
| Length | 1200 [mm] |
| Outer diameter | Unknown |
| Built-in length | Unknown |
| Built-in width | Unknown |
| Built-in height/depth | Unknown |
| Built-in diameter | Unknown |
| Type of wiring | Unknown |
| Number of poles | 2 |
| Conductor cross section | Unknown |
| Total harmonic distortion (THD) | Unknown |
| Connection type | Screw terminal |
| Photobiological safety according to EN 62471 | Unknown |
| Unified Glare Ratio (UGR) | Unknown |
| Colour of light adjustable | No |

| | |
|----------------------------------|----|
| Luminous flux adjustable | No |
| Beam angle adjustable | No |
| Operation by Bluetooth | No |
| Compatible with Apple HomeKit | No |
| Compatible with Google Assistant | No |
| Compatible with Amazon Alexa | No |
| IFTTT support available | No |

Ordering information

| | |
|-----------------------|-----|
| Order unit | One |
| Minimum quantity | 1 |
| Quantity interval | 1 |
| Content unit | One |
| Content unit quantity | 1 |

Attachments

| | |
|----------------------|---|
| Product data sheet | https://b2b.kanlux.pl/storage/products/technicznaErp/pl/31411.pdf |
| Product data sheet | https://epim.one/product-card/pdf/LPC6Gnltt3eK2UIlotfzZAcU7raPddcu/lang/en |
| Product data sheet | https://epim.one/product-card/pdf/LPC6Gnltt3eK2UIlotfzZAcU7raPddcu/lang/pl |
| Main product picture | https://files.epim.one/pekra/foto/31411.jpg |

Related product

| | |
|--------------------|-----------------|
| Related product ID | 8595665314101 |
| Relation type | Similar product |