



General information

Product ID	5908312594062
GTIN	5908312594062
Alt. product ID by supplier	BIS-402
Manufacturer name	FiF
Manufacturer short name	FF
Manufacturer product ID	BIS-402
Net length	0.095 m
Net width	0.07 m
Net height	0.02 m
Net weight	0.05 kg
Net volume	133000 mm ³

ETIM description

Class	Latching relay (EC000188)
Group	Devices for distribution board-/surface mounting (EG000062)
Function	Electronic switch
Mounting method	Flush-mounted
Built-in depth	13 [mm]
Number of contacts as normally open contact	1
Number of contacts as normally closed contact	0
Number of contacts as change-over contact	0
Control voltage 1	230..230 [V]
Type of control voltage 1	AC
Frequency control voltage 1	50..50 [Hz]
Control voltage 2	0..0 [V]

Frequency control voltage 2	0..0 [Hz]
Rated switch current	8 [A]
Supply voltage	230..230 [V]
Voltage type (supply voltage)	AC
Max. incandescent lamp load	1500 [W]
Max. load fluorescent lamp	650 [VA]
Max. load fluorescent lamp (Duo circuit)	650 [VA]
Max. load fluorescent lamp (parallel compensated)	500 [VA]
Max. switching current (cos phi = 0.6)	5 [A]
Suitable for manual operation	No

Ordering information

Order unit	One
Minimum quantity	1
Quantity interval	1
Content unit	One
Content unit quantity	1

Attachments

Product data sheet	https://epim.one/product-card/pdf/NZlwoneE9dHOOHkhnwFPr20HaElowiEe/lang/en
Product data sheet	https://epim.one/product-card/pdf/NZlwoneE9dHOOHkhnwFPr20HaElowiEe/lang/pl
Declaration	https://files.epim.one/etimone/FF/UE_FF003_18_BIS_dek_zgod_C E.pdf
Main product picture	https://files.epim.one/pekra/FF/FF_BIS-402.jpeg
Manual	https://files.epim.one/etimone/FF/FF_BIS-402_inst_D180112_PL_PDF.pdf
Others	http://www.fif.com.pl/przekazniki-bistabilne/40-przekaznik-bista bilny-bis-402.html