



General information

Product ID	8592765083333
GTIN	8592765083333
Manufacturer name	NOARK
Manufacturer short name	NOARK
Manufacturer product ID	108333
Net length	0.083 m
Net width	0.068 m
Net height	0.07 m
Net weight	0.356 kg
Net volume	395080 mm ³

ETIM description

Class	Residual current circuit breaker (RCCB) (EC000003)
Group	Circuit breakers and fuses (EG000020)
Number of poles	4
Rated voltage	400 [V]
Rated current	63 [A]
Rated fault current	0.03 [A]
Rated insulation voltage Ui	500 [V]
Rated impulse withstand voltage Uimp	6 [kV]
Mounting method	DIN rail
Leakage current type	AC
Selective protection	No
Short-time delayed tripping	No
Short-circuit breaking capacity (Icw)	6 [kA]
Surge current capacity	3 [kA]

Voltage type	AC
With interlocking device	No
Frequency	50 Hz
Additional equipment possible	No
Degree of protection (IP)	IP20
Width in number of modular spacings	4
Built-in depth	79 [mm]
Ambient temperature during operating	-25..60 [°C]
Pollution degree	2
Connectable conductor cross section multi-wired	1..25 [mm²]
Connectable conductor cross section solid-core	1..25 [mm²]
Explosion-proof	No

Ordering information

Order unit	One (unit)
Minimum quantity	1
Quantity interval	1
Content unit	One (unit)
Content unit quantity	1

Attachments

Data sheet	https://epim.one/product-card/pdf/NZjkExaNAsPsO8zB3utVmTu5basfbYgl/lang/en
Data sheet	https://epim.one/product-card/pdf/NZjkExaNAsPsO8zB3utVmTu5basfbYgl/lang/pl
Main product picture	https://files.epim.one/pekra/foto/Ex9L-N_4P.jpg