



General information

|                         |                        |
|-------------------------|------------------------|
| Product ID              | 8592765083333          |
| GTIN                    | 8592765083333          |
| Manufacturer name       | NOARK                  |
| Manufacturer short name | NOARK                  |
| Manufacturer product ID | 108333                 |
| Net length              | 0.083 m                |
| Net width               | 0.068 m                |
| Net height              | 0.07 m                 |
| Net weight              | 0.356 kg               |
| Net volume              | 395080 mm <sup>3</sup> |

ETIM description

|                                       |                                                    |
|---------------------------------------|----------------------------------------------------|
| Class                                 | Residual current circuit breaker (RCCB) (EC000003) |
| Group                                 | Circuit breakers and fuses (EG000020)              |
| Number of poles                       | 4                                                  |
| Rated voltage                         | 400 [V]                                            |
| Rated current                         | 63 [A]                                             |
| Rated fault current                   | 0.03 [A]                                           |
| Rated insulation voltage Ui           | 500 [V]                                            |
| Rated impulse withstand voltage Uimp  | 6 [kV]                                             |
| Mounting method                       | DIN rail                                           |
| Leakage current type                  | AC                                                 |
| Selective protection                  | No                                                 |
| Short-time delayed tripping           | No                                                 |
| Short-circuit breaking capacity (Icw) | 6 [kA]                                             |
| Surge current capacity                | 3 [kA]                                             |

|                                                 |              |
|-------------------------------------------------|--------------|
| Voltage type                                    | AC           |
| With interlocking device                        | No           |
| Frequency                                       | 50 Hz        |
| Additional equipment possible                   | No           |
| Degree of protection (IP)                       | IP20         |
| Width in number of modular spacings             | 4            |
| Built-in depth                                  | 79 [mm]      |
| Ambient temperature during operating            | -25..60 [°C] |
| Pollution degree                                | 2            |
| Connectable conductor cross section multi-wired | 1..25 [mm²]  |
| Connectable conductor cross section solid-core  | 1..25 [mm²]  |
| Explosion-proof                                 | No           |

## Ordering information

|                       |            |
|-----------------------|------------|
| Order unit            | One (unit) |
| Minimum quantity      | 1          |
| Quantity interval     | 1          |
| Content unit          | One (unit) |
| Content unit quantity | 1          |

## Attachments

|                      |                                                                                                                                                                     |
|----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Data sheet           | <a href="https://epim.one/product-card/pdf/NZjkExaNAsPsO8zB3utVmTu5basfbYgl/lang/en">https://epim.one/product-card/pdf/NZjkExaNAsPsO8zB3utVmTu5basfbYgl/lang/en</a> |
| Data sheet           | <a href="https://epim.one/product-card/pdf/NZjkExaNAsPsO8zB3utVmTu5basfbYgl/lang/pl">https://epim.one/product-card/pdf/NZjkExaNAsPsO8zB3utVmTu5basfbYgl/lang/pl</a> |
| Main product picture | <a href="https://files.epim.one/pekra/foto/Ex9L-N_4P.jpg">https://files.epim.one/pekra/foto/Ex9L-N_4P.jpg</a>                                                       |