



## General information

|                         |                        |
|-------------------------|------------------------|
| Product ID              | 5905339338815          |
| GTIN                    | 5905339338815          |
| Supplier                | Kanlux                 |
| Manufacturer name       | KANLUX                 |
| Manufacturer short name | KANL                   |
| Manufacturer product ID | 33881                  |
| Brand name              | Kanlux                 |
| Net length              | 0.165 m                |
| Net width               | 0.135 m                |
| Net height              | 0.03 m                 |
| Net weight              | 0.324 kg               |
| Net volume              | 668250 mm <sup>3</sup> |

## ETIM description

|                                      |                                      |
|--------------------------------------|--------------------------------------|
| Class                                | Downlight/spot/floodlight (EC001744) |
| Group                                | Luminaires (EG000027)                |
| Suitable for surface mounting        | Yes                                  |
| Suitable for built-in mounting       | No                                   |
| Suitable for wall mounting           | Yes                                  |
| Suitable for suspended mounting      | Yes                                  |
| Suitable for ceiling mounting        | Yes                                  |
| Suitable for traverse mounting       | No                                   |
| Suitable for pedestal/floor mounting | Yes                                  |
| Suitable for light-track mounting    | No                                   |
| Suitable for clamp-mounting          | No                                   |

|                                                      |                                         |
|------------------------------------------------------|-----------------------------------------|
| Suitable for low voltage cable system                | No                                      |
| Adjustability                                        | Swivelling                              |
| With movement sensor                                 | No                                      |
| With light sensor                                    | No                                      |
| Lamp type                                            | LED not exchangeable                    |
| With light source                                    | Yes                                     |
| Suitable for number of light sources                 | 1                                       |
| Housing material                                     | Aluminium                               |
| Surface protection                                   | Powder coating                          |
| Housing colour                                       | Black                                   |
| Material cover                                       | Glass opal                              |
| Surface brushed                                      | No                                      |
| Voltage type                                         | AC                                      |
| Nominal voltage                                      | 220..240 [V]                            |
| Type of control gear                                 | LED operating device current-controlled |
| With control gear                                    | Yes                                     |
| Exchangeable control gear                            | No                                      |
| Dimming 0-10 V                                       | No                                      |
| Dimming 1-10 V                                       | No                                      |
| Dimming DALI-2                                       | No                                      |
| Dimming DALI                                         | No                                      |
| Dimming DMX                                          | No                                      |
| Dimming DSI                                          | No                                      |
| Dimming potentiometer (integrated)                   | No                                      |
| Dimming LineSwitch                                   | No                                      |
| Dimming manufacturer's proprietary system            | No                                      |
| Dimming mains voltage modulation                     | No                                      |
| Dimming phase cut-off (trailing edge)                | No                                      |
| Dimming phase cut-on (leading edge)                  | No                                      |
| Light distributor                                    | Reflector                               |
| Light outlet                                         | Direct                                  |
| Rated lifetime L70/B50 at 25 °C                      | 50000 [h]                               |
| Impact strength                                      | IK07                                    |
| Protection class according to IEC 61140              | I                                       |
| Rated ambient temperature according to IEC 62722-2-1 | -30..50 [°C]                            |
| Suitable for lamp power                              | 20..20 [W]                              |
| Max. system power                                    | 20 [W]                                  |
| Colour of light                                      | White                                   |
| Colour temperature                                   | 4000..4000 [K]                          |
| Colour rendering index CRI                           | 80-89                                   |
| Rated luminous flux according to IEC 62722-2- 1      | 2600..2600 [lm]                         |
| Power factor                                         | 0.9                                     |

|                 |          |
|-----------------|----------|
| Length          | 165 [mm] |
| Width           | 135 [mm] |
| Height/depth    | 30 [mm]  |
| Type of wiring  | Ending   |
| Number of poles | 3        |
| Connection type | Other    |

## Ordering information

|                       |            |
|-----------------------|------------|
| Order unit            | One (unit) |
| Minimum quantity      | 1          |
| Quantity interval     | 1          |
| Content unit          | One (unit) |
| Content unit quantity | 1          |

## Attachments

|                      |                                                                                                                                                                     |
|----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Data sheet           | <a href="https://epim.one/product-card/pdf/RMk79zfnroYbj9WOpuaaeS3as37nYwcS/lang/en">https://epim.one/product-card/pdf/RMk79zfnroYbj9WOpuaaeS3as37nYwcS/lang/en</a> |
| Data sheet           | <a href="https://epim.one/product-card/pdf/RMk79zfnroYbj9WOpuaaeS3as37nYwcS/lang/pl">https://epim.one/product-card/pdf/RMk79zfnroYbj9WOpuaaeS3as37nYwcS/lang/pl</a> |
| Main product picture | <a href="https://files.epim.one/pekra/foto/33881.jpg">https://files.epim.one/pekra/foto/33881.jpg</a>                                                               |

## Related product

|                    |               |
|--------------------|---------------|
| Related product ID | 8592920035160 |
| Relation type      | Accessory     |