

## General information

Product ID	8592765111487
GTIN	8592765111487
Manufacturer name	NOARK
Manufacturer short name	NOARK
Manufacturer product ID	111148
Net length	0.083 m
Net width	0.012 m
Net height	0.077 m
Net weight	0.150 kg
Net volume	76692 mm <sup>3</sup>

## ETIM description

Class	Earth leakage circuit breaker (EC000905)
Group	Circuit breakers and fuses (EG000020)
Number of poles (total)	2
Number of protected poles	1
Rated voltage	240 [V]
Rated insulation voltage $U_i$	500 [V]
Rated impulse withstand voltage $U_{imp}$	4 [kV]
Rated current	16 [A]
Rated fault current	0.03 [A]
Leakage current type	AC
Current limiting class	3
Rated short-circuit breaking capacity according to EN 61009	6 [kA]
Disconnection characteristic	Undelayed
Frequency	50 Hz
Release characteristic	B
Concurrently switching neutral conductor	Yes
With interlocking device	No
Overvoltage category	3
Pollution degree	2
Width in number of modular spacings	1
Built-in depth	77 [mm]
Degree of protection (IP)	IP20

## Ordering information

Order unit	One
Minimum quantity	1
Quantity interval	1
Content unit	One
Content unit quantity	1

## Attachments

Product data sheet	<a href="https://epim.one/product-card/pdf/YoP5DKN8hkA8PTtoeHZ674844896252c/lang/en">https://epim.one/product-card/pdf/YoP5DKN8hkA8PTtoeHZ674844896252c/lang/en</a>
Product data sheet	<a href="https://epim.one/product-card/pdf/YoP5DKN8hkA8PTtoeHZ674844896252c/lang/pl">https://epim.one/product-card/pdf/YoP5DKN8hkA8PTtoeHZ674844896252c/lang/pl</a>
Main product picture	<a href="https://noark-electric.pl/_next/image?url=https%3A%2F%2Fd1nvgv4bagkf76.cloudfront.net%2F15796%2Fconversions%2Fex9nl-e-optimized.webp&amp;w=1920&amp;q=75">https://noark-electric.pl/_next/image?url=https%3A%2F%2Fd1nvgv4bagkf76.cloudfront.net%2F15796%2Fconversions%2Fex9nl-e-optimized.webp&amp;w=1920&amp;q=75</a>