



General information

Product ID	5908312598275
GTIN	5908312598275
Alt. product ID by supplier	BIS-416
Manufacturer name	FiF
Manufacturer short name	FF
Manufacturer product ID	BIS-416
Net length	0.043 m
Net width	0.048 m
Net height	0.02 m
Net weight	0.05 kg
Net volume	41280 mm ³

ETIM description

Class	Latching relay (EC000188)
Group	Devices for distribution board-/surface mounting (EG000062)
Function	Electronic switch
Mounting method	Flush-mounted
Built-in depth	20 [mm]
Number of contacts as normally open contact	2
Number of contacts as normally closed contact	0
Number of contacts as change-over contact	0
Control voltage 1	230..230 [V]
Type of control voltage 1	AC
Frequency control voltage 1	50..50 [Hz]
Control voltage 2	0..0 [V]

Frequency control voltage 2	0..0 [Hz]
Rated switch current	0.005 [A]
Supply voltage	230..230 [V]
Voltage type (supply voltage)	AC
Max. incandescent lamp load	1000 [W]
Max. load fluorescent lamp	500 [VA]
Max. load fluorescent lamp (parallel compensated)	250 [VA]
Max. switching current (cos phi = 0.6)	8 [A]
Suitable for manual operation	No

Ordering information

Order unit	One (unit)
Minimum quantity	1
Quantity interval	1
Content unit	One (unit)
Content unit quantity	1

Attachments

Data sheet	https://epim.one/product-card/pdf/gnXZJ5rryZYIFY3zH4ljdx6LYvOmAF0J/lang/en
Data sheet	https://epim.one/product-card/pdf/gnXZJ5rryZYIFY3zH4ljdx6LYvOmAF0J/lang/pl
Main product picture	https://www.fif.com.pl/926-thickbox_default/przekaznik-bistabilny-bis-416-230-v.jpg
Manual	https://files.epim.one/pekra/pdf/UE_FF003_23_BIS_dek_zgod_CE_LVD EMC_RoHS.pdf