



## General information

Product ID	5905339331717
GTIN	5905339331717
Supplier	Kanlux
Manufacturer name	KANLUX
Manufacturer short name	KANL
Manufacturer product ID	33171
Brand name	Kanlux
Net length	1.5 m
Net width	0.073 m
Net height	0.063 m
Net weight	1.21 kg
Net volume	6898500 mm <sup>3</sup>
Discount group ID	Brak
Bonus group ID	Brak
Customs commodity code	94051040

## ETIM description

Class	Ceiling-/wall luminaire (EC002892)
Group	Luminaires (EG000027)
Suitable for wall mounting	Yes
Suitable for suspended mounting	No
Suitable for ceiling mounting	Yes
Suitable for built-in mounting	No
Suitable for surface mounting	Yes
Suitable for light line configuration	No

Lamp type	LED not exchangeable
With light source	Yes
Suitable for number of light sources	1
Lamp holder	Other
Housing material	Plastic
Surface protection housing	Untreated
Housing colour	White
Material cover	Plastic, opal
Type of grid	None
Voltage type	AC
Nominal voltage	220..230 [V]
Nominal current	Unknown
Exchangeable control gear	No
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI	No
Dimming DALI-2	No
Dimming DMX	No
Dimming DSI	No
Dimming manufacturer's proprietary system	No
Dimming mains voltage modulation	No
Dimming phase cut-off (trailing edge)	No
Dimming phase cut-on (leading edge)	No
Dimming programmable	No
Dimming potentiometer (integrated)	No
Dimming RF	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming with push-button	No
Light distributor	Unknown
Light distribution	Symmetric
Beam angle	Unknown
Colour consistency (McAdam ellipse)	Unknown
Light outlet	Unknown
Rated lifetime L70/B50 at 25 °C	Unknown
Lumen maintenance at median useful life of 35,000 h at 25 °C ambient (tq)	Unknown
Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq)	Unknown
Lumen maintenance at median useful life of 75,000 h at 25 °C ambient (tq)	Unknown
Failure rate at median useful life of 35,000 h at 25 °C ambient (tq)	Unknown

Failure rate at median useful life of 50,000 h at 25 °C ambient (tq)	Unknown
Failure rate at median useful life of 75,000 h at 25 °C ambient (tq)	Unknown
Max. number of luminaires per miniature circuit breaker B16 (MCB)	Unknown
Max. number of luminaires per miniature circuit breaker C16 (MCB)	Unknown
Degree of protection (NEMA)	Unknown
Impact strength	Unknown
Protection class according to IEC 61140	I
Rated ambient temperature according to IEC 62722-2-1	-20..40 [°C]
Suitable for emergency lighting	No
With movement sensor	No
With light sensor	No
Covering of the luminaire with thermally insulating material possible	No
With air slots	No
Filament test according to IEC 60695-2-11	Unknown
Suitable for lamp power	75..75 [W]
Max. system power	75 [W]
Rated luminous flux according to IEC 62722-2- 1	10000..10000 [lm]
Colour of light	White
Colour temperature	4000..4000 [K]
Flickering value Pst LM	Unknown
Colour rendering index CRI	Unknown
Power factor	Unknown
Stroboscope effect value SVM	Unknown
Constant light output (CLO)	No
Width	72 [mm]
Height/depth	63 [mm]
Length	1500 [mm]
Outer diameter	Unknown
Built-in length	Not applicable
Built-in width	Not applicable
Built-in height/depth	Not applicable
Built-in diameter	Not applicable
Type of wiring	Unknown
Number of poles	2
Conductor cross section	Unknown
Total harmonic distortion (THD)	Unknown
Connection type	Other
Photobiological safety according to EN 62471	Unknown
Unified Glare Ratio (UGR)	Unknown

Colour of light adjustable	No
Luminous flux adjustable	No
Beam angle adjustable	No
Operation by Bluetooth	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No

## Ordering information

Order unit	One (unit)
Minimum quantity	1
Quantity interval	1
Content unit	One (unit)
Content unit quantity	1

## Attachments

Data sheet	<a href="https://epim.one/product-card/pdf/s6HFjR1kMhDoW0eOvParVd24pNa8Trk5/lang/en">https://epim.one/product-card/pdf/s6HFjR1kMhDoW0eOvParVd24pNa8Trk5/lang/en</a>
Data sheet	<a href="https://epim.one/product-card/pdf/s6HFjR1kMhDoW0eOvParVd24pNa8Trk5/lang/pl">https://epim.one/product-card/pdf/s6HFjR1kMhDoW0eOvParVd24pNa8Trk5/lang/pl</a>
Main product picture	<a href="https://files.epim.one/pekra/foto/33171.jpg">https://files.epim.one/pekra/foto/33171.jpg</a>