



General information

Product ID	9010238060746
GTIN	9010238060746
Manufacturer name	EATON
Manufacturer short name	EATON
Manufacturer product ID	195121
Net length	0.083 m
Net width	0.034 m
Net height	0.07 m
Net weight	0.212 kg
Net volume	197540 mm ³

ETIM description

Class	Earth leakage circuit breaker (EC000905)
Group	Circuit breakers and fuses (EG000020)
Number of poles (total)	2
Number of protected poles	1
Rated voltage	230 [V]
Rated insulation voltage Ui	500 [V]
Rated impulse withstand voltage Uimp	4 [kV]
Rated current	16 [A]
Rated fault current	0.03 [A]
Mounting method	DIN rail
Leakage current type	AC
Current limiting class	3
Rated short-circuit breaking capacity according to EN 61009	6 [kA]

Rated short-circuit breaking capacity according to IEC 60947-2	0 [kA]
Rated short-circuit breaking capacity Icn according to EN 61009-1	6 [kA]
Disconnection characteristic	Undelayed
Surge current capacity	0.25 [kA]
Voltage type	AC
Frequency	50 Hz
Release characteristic	B
Concurrently switching neutral conductor	Yes
With interlocking device	No
Overvoltage category	3
Pollution degree	2
Ambient temperature during operating	-25..40 [°C]
Width in number of modular spacings	2
Built-in depth	69.5 [mm]
Anti- nuisance tripping version	No
Degree of protection (IP)	IP20
Connectable conductor cross section solid-core	1..25 [mm²]
Connectable conductor cross section multi-wired	1..25 [mm²]

Ordering information

Order unit	One (unit)
Minimum quantity	1
Quantity interval	1
Content unit	One (unit)
Content unit quantity	1

Attachments

Data sheet	https://epim.one/product-card/pdf/wupNI6ZDLLT3B1tG0hhwLEhThZy9I0Ph/lang/pl
Declaration (other)	https://files.epim.one/etimone/EATON/hnb_en.pdf
Main product picture	https://files.epim.one/pekra/EATON/EATON_195121.jpeg

Related product

Related product ID	4015082484392
Relation type	Accessory